

REWATEC®



FEATURES

- Injected toilet cover
- Lifting rings
- Toilet paper holder
- Lock with key
- Easy cleaning
- Chemical toilet or with connection to the sewer network
- English or Turkish WC
- Ideal for events, construction sites, public works, areas of difficult access or areas with or without a sewer network

DIMENSIONS

MECABI 1200 mm / 1200 mm / 2300 mm | Weight: 115 kg

MECAPLAST 1200 mm / 1200 mm / 2400 mm | Weight: 130 kg



WC MECAPLAST | MECABI

Features	Mecabi		Mecaplast	
	Chemical	Connection to sewer network	Chemical	Connection to sewer network
A English WC capacity 200 L with water injector	✓	✓		
B Turkish WC capacity 200 L with water injector			✓	✓
C Interior lock with vacant/occupied indicator	✓	✓	✓	✓
D Male/female identifier	✓	✓	✓	✓
E Door with interior mirror and coat hanger	✓	✓	✓	✓
F Spring-equipped door for smooth closing	✓	✓	✓	✓
G Ventilation grill	✓	✓	✓	✓
H Urinal	✓	✓		
I Water reservoir and lavatory	✓	✓	✓	✓
J Foot pump for flushing	✓	✓	✓	✓
K Toilet paper holder	✓	✓	✓	✓
L 4x Lifting rings	✓	✓	✓	✓
M Wall pass-through and 1½" valve for suction (optional)	✓		✓	

Available with granite white walls and blue, green or red pillars.



OPERATING PRINCIPLE

1. Bring at the place of use and visually check the general condition.
2. Fill the WC reservoir (200 L capacity) with 30 L of clean water and liquid sanitary additive or tablets.
Notice: The chemical reduces odours and liquefies organic matter.
3. Adjust the dosage of the product in case of high temperatures or very spaced cleaning.
4. Fill the reservoir with clean water for hand washing through the top hole.

5. When the WC reservoir is full it must be emptied:
 - Manually to a place authorised for this purpose.
 - Pumped, directly from WC reservoir to own container.

Attention:

All discharges must take place in areas licensed and/or approved for this purpose. Never in nature.