

Guide for professionals

ECOFLO REWATEC









People and Technologies making a difference

Premier Tech brings to life products that help feed, protect, and improve our world:

- founded in 1923
- family business
- 3,000 team members in North America
- 5,200 team members worldwide in 28 countries

PREMIER TECH

- 25 manufacturing facilities in North America
- 48 factories in 16 countries

Through its Water and Environment business group, Premier Tech is a world leader in designing and manufacturing sustainable local solutions for:

Wastewater treatment

Residential





Rainwater management



Together, we make green technologies accessible and continuously innovate to create lasting solutions.

Premier Tech's 360° support

Since 1995, professionals have been the heart of our business.





IMMEDIATE ASSISTANCE

Experts available Monday to Friday to answer your questions.



IN-PERSON FIELD SUPPORT

Experts go on-site to assist in resolving challenges.



Largest network of local partners to maintain systems and honor warranties.

ACCESSIBLE TRAINING

Online and in-person training programs for installers, designers, and regulators.



FULL CUSTOMER SUPPORT

Our team supports you by assisting homeowners directly.



PRO SPACE

Quickly find all the documents you need in one place.

- installation guides
- technical data sheets
- technical drawings
- and more

Ecoflo[®] is how we make a sustainable difference. Together.

Join us in the movement to make the world a better, more sustainable place. Protect your client's property and the environment by recommending Ecoflo, the most eco-responsible septic system brand.

SUSTAINABLE FILTER

Our systems remove pollutants with a filter made of coconut husk fragments, or a combination of coco and peat. Both materials are natural and compostable, and coco is 100% renewable.

COCO REGENERATES



It is not just the fruit of the coconut that matters. Coconut husks are a valuable resource as well. That is why we give them second life as a wastewater filtering medium.

Each filter offers years of effective performance.

When a filter's treatment days are over, the story of coco continues. We give it third life as compost that regenerates soils and forests near you.

Ecoflo

Linear biofilter

We reinvented combined treatment and dispersal

You choose combined treatment and dispersal because it is reliable. It makes sense for many sites. But the products on the market are not perfect. They have some problems. Now we have solutions.

YOU WANT

- Alternatives to C33 sand
- Uniform wastewater distribution
- Quick and headache-free installation
- A reusable system
- A repairable system

> WE OFFER

- Multiple sand options in smaller quantities
- An optional distribution box with energy-free dosing
- Integrated distribution channels that replace perforated pipes
- Reusable hard components and a renewable filtering medium
- System access



The Ecoflo linear biofilter allows you to choose C33 alternatives in smaller quantities for your installation. Plus, you get ease of access and integrated distribution channels that eliminate the need for perforated pipes.



ECOFLO

Homeowner benefits

PEACE OF MIND

- zero-energy treatment
- 24/7 autonomous operation
- minimal maintenance

DISCREET INSTALLATION

- smaller than a traditional drain field
- integrates seamlessly into landscape
- noiseless and odorless

EASY TO REPAIR

- accessible for troubleshooting
- reusable hard components
- minimal excavation process

Linear biofilter

HOMEOWNER TOUCHPOINT

After each installation, we contact new owners to explain the Ecoflo linear biofilter's dos and don'ts. We make sure their septic system is working perfectly, and we answer their questions.

MAINTENANCE

We have a network of partners annually trained by us to protect your client's investment in their Ecoflo linear biofilter.

COCO BENEFITS YOUR PROJECT

The Ecoflo linear biofilter's coco filter offers exceptional treatment quality for wastewater. This reduces the cost of your project by:

- giving you more options for cheaper, locally sourced sands
- using sand in smaller quantities
- absorbing contaminants to preserve the sand layer

Coco is also renewable, natural, and 100% compostable!





Linear biofilter

Specifications

TREATMENT PERFORMANCE

	Influent	ANSI/NSF Standard 40 Class 1	Ecoflo linear biofilter effluent*
TSS	231 mg/L	25 mg/L	3.9 mg/L
CBOD₅	199 mg/L	30 mg/L	8.1 mg/L
рН	7.0	6.0-9.0	6.9

* Model EL15.

DISTRIBUTION OPTIONS

Gravity



Pump to gravity



Low pressure





SCAN ME TO DOWNLOAD THE INSTALLATION GUIDE PDF



SCAN ME TO SEE THE INSTALLATION GUIDE VIDEO



SUGGESTED CONFIGURATIONS

The Ecoflo linear biofilter can be installed in a raised, partially raised, or in-ground configuration.







EXAMPLES: NUMBER OF MODULES REQUIRED

Design flow USG/d (L/d)	One treatment line	Two treatment lines	Three treatment lines	Four treatment lines	Five treatment lines
400 (1,500)	15	2 x 8	3 x 5	4 x 4	5 x 3
500 (1,800)	18 🕑	2 x 9	3 x 6	4 x 5	5 x 4
600 (2,200)	22 🕑	2 x 11	3 x 8	4 x 6	5 x 5
700 (2,600)	26 🕑	2 x 13	3 x 9	4 x 7	5 x 6
800 (3,000)	30 🕑	2 x 15	3 x 10	4 x 8	5 x 6
900 (3,400)	34 🕑	2 x 17	3 x 12	4 x 9	5 x 7

P EL15 model, low-pressure distribution required.

MINIMUM DISTANCES TO RESPECT

The Ecoflo linear biofilter must be installed in a location:

- free of motorized traffic
- unlikely to be submerged
- accessible to service and maintenance
- 6' (2 m) from any tree
- conforming with local regulations

ECOFLO[®]

Linear biofilter

The parts



Protective chamber

Effective length		3' 10-3/4" (1,183 mm)
Width	B	2' 2" (660 mm)
Height	G	11-1/2" (292 mm)
Overall length	D	4' 5-1/2" (1,359 mm)
Inlet invert	0	8-1/4" (210 mm)
Channel width	6	4-1/2" (114 mm)
Inner width	G	1' 4-1/4" (410 mm)
Weight*		23.3 lb (10.6 kg)
Material		ABS
-		

* Weights are for handling and lifting purposes only. They are approximate and non-binding.

Caps

	Inlet cap	End cap
Length 🛛 🔕	7-3/4" (195 mm)	1' 4-1/4" (415 mm)
Width 🔋	2' 2-3/4"	(267 mm)
Height G	1' 1-1/8" (333 mm)	
Inlet invert (from sand layer) 🏾 🖸	8-1/4" (210 mm)	
Inlet diameter	4-1/2" (114 mm)	
Weight*	4.8 lb (2.19 kg)	6 lb (2.7 kg)
Material	A	BS

* Weights are for handling and lifting purposes only. They are approximate and non-binding.

Top cover

Length 🙆	3' 10-3/4" (1,183 mm)	
Width 🛛 🕒	8-1/4" (208 mm)	
Height G	1-7/8" (47 mm)	
Weight*	4.2 lb (1.9 kg)	
Material	ABS	

 * Weights are for handling and lifting purposes only. They are approximate and non-binding.







Filtration pad

Width	1' 3-3/4" (400 mm)
Overall height	8" (200 mm)
Height at center G	6-3/4" (173 mm)
Effective length	3' 10-3/4" (1,183 mm)
Overall length	4' (1,219 mm)
Weight*	19.8 lb (9 kg)
Material	Coco fibers and latex

 * Weights are for handling and lifting purposes only. They are approximate and non-binding.

Dosing device

Hydraulic capacity	925 gpd (3,500 L/d)
Discharge	Gravity
Number of outlets	1 to 5
Length 🛛 💧	5' 2" (1,575 mm)
Width	2' 9-1/2" (850 mm)
Total height assembled G	2' 1-3/8" (645 mm)
Inlet height from top	1' 3-1/4" (389 mm)
Outlet height from top	1' 10" (539 mm)
Upper lid height 🕞	1' 6-1/4" (465 mm)
Dose height G	3-1/8" (80 mm)
Residual water height	2-1/4" (55 mm)
Overflow height	1' 8" (507 mm)
Transportation mode height	1' 7-3/4" (500 mm)
Access diameter	2' (600 mm)
Access lid outside diameter	2' (600 mm)
Total weight*	88 lb (40 kg)
Nominal dosing volume	18.5 gal (70 L)
Material	Polyethylene

 * Weights are for handling and lifting purposes only. They are approximate and non-binding.

MAIN DESIGN PARAMETERS

Design parameter	Criteria
Linear design loading rate applied to treatment modules	6.80 gpd/ft 84 L/m · d
Design loading rate applied per treatment module	26.4 gal/module 100 L/module
Maximum length of row for gravity or pump-to-gravity system	60' (18 m) (15 modules)
Maximum length of row for low-pressure distribution system	100' (30 m) (25 modules)
Minimum sand layer height beneath filtration pads	6" (150 mm)
Minimum width of sand layer beneath filtration pads	34'' (864 mm)
Minimum distance from end of filtration pads line to edge of absorption area	6" (150 mm) minimum
Width of filtration pads	15 3/4'' (400 mm)
Center-to-center spacing between rows of modules	34" (864 mm) minimum
Module height	13'' (330 mm)
FI 15 model	













Gravity outlet

Inline screen filter

THE #1 COMPACT FILTER CHOICE!

QUICK INSTALLATION

- ready-to-use models
- easy-to-follow instructions
- can be installed in just one day

> MODELS FOR ANY SITE

- options for all soil conditions
- pumped or gravity discharge
- compact models

> PRODUCT AVAILABILITY

- 140 depots across North America
- quality-controlled inventory
- reliable order tracking

> 10-YEAR TOTAL WARRANTY

- all treatment-related parts and labor
- proper functioning of the filtering medium and its treatment performance
- no clogging or excess sludge

OUTPERFORMS STANDARDS

NSF/ANSI standard 40				
Parameter Requirement* Ecoflo compa biofilter				
TSS	< 25 mg/L	8 mg/L**		
CBOD₅ < 30 mg/L		6 mg/L**		
Fecal coliforms	No requirement	_		

30-day average.

** EC7 model series results.

[†] With 100% coconut husk fragment filtering medium.

LOWEST CARBON FOOTPRINT

From production and shipping to installation, maintenance, and usage, the Ecoflo biofilter has the lowest carbon footprint of any product on the market.

Total after 50-year life cycle



Notes

- Based on analysis of septic installations in Pennsylvania.
- Systems installed in soil with percolation rate of 60 mpi and rated for four bedrooms.
- Distances between installations and required materials assumed to be 40 miles
- for filtration sand and stone, 20 miles for backfill.
- Ecoflo biofilter installations include final dispersal to at-grade bed.

BEST LONG-TERM INVESTMENT

- maintains the selling value of your client's property
- no energy bills for wastewater treatment
- no high-priced repairs or hidden costs
- no full-system replacements

HH

ECOFLO

Compact biofilter

Polyethylene

Solution for

- 1,350 US gal/d maximum capacity
- sites with limited space
- simple and quick installations

Advantages

- ready to use
- ready to use
- compact and lightweight

• integrated pumping chamber

Concrete

Solution for

- 1,200 US gal/d maximum capacity
- all soil types
- high water tables

Advantages

- high-strength tank
- install in groundwater up to the inlet pipe (pumped models only)
- integrated pumping chamber



Polyethylene • Pack

Solution for

- 750 US gal/d maximum capacity
- sites with limited space

Advantages

- minimal final footprint
- primary treatment tank with baffle wall
- one excavation
- integrated pumping chamber

Fibreglass

Solution for

- 1,400 US gal/d maximum capacity
- · sites with limited space
- remote locations

Advantages

- infiltration bed under the unit
- compact and light
- gravity treatment | no energy



SCAN ME FOR THE FIBREGLASS SPECIFICATIONS



Pack

F

A product supported by the manufacturer

HOMEOWNER TOUCHPOINT

After each installation, we invite new owners to an informal session to explain the Ecoflo biofilter's do's and don'ts, how to make sure their septic system is working properly, and to answer their questions.

ANNUAL MAINTENANCE

We offer annual training to our network of partners to maximize the lifespan of your client's coco filter and to protect their investment in their septic system.

- 15-point inspection
- · coco filter aeration to promote healthy bacterial activity
- · coco filter scarification to ensure optimal biofiltration

SYSTEM REFURBISHMENT AT A FRACTION OF THE PRICE

Renewing the filtering medium is as good as getting a brand new system! All septic systems clog, and while the Ecoflo biofilter's all-natural filtering medium can extend beyond 15 years, it is no exception. But here's the good part:

- no excavation required
- no damage to landscaping
- 100% compostable filtering media
- completed within 2 hours
- renewal of original warranty





ECOFLO Polyethylene • Pack



	2.8	3.4	4.1	
	EC7-500-P-G/P-PACK	EC7-600-P-G/P-PACK	EC7-750-P-G/P-PACK	
Hydraulic capacity	500 US gal/d	600 US gal/d	750 US gal/d	
Primary tank volume	800 US gal	1,000 US gal	1,250 US gal	
Length (A	10' 2-3/4"	11' 7-3/4"	13' 3-1/2"	
Width B	8' 1-3/4"			
Height Includes 12" of risers	5' 9-3/4"			
Inlet height of primary tank prom bottom	4' 2-1/2"			
Gravity water outlet height 😝 1-1/2"				
Pumped water outlet height 🛛 😝	3' 9"			
Additional riser allowed	6"			
Weight Includes internal components and coco filter	1,675 lb	1,870 lb	2,090 lb	
Built-in effective volume available for dosing Pumped discharge models only	160 US gal	180 US gal	200 US gal	
Emergency storage above alarm float	545 US gal	665 US gal	760 US gal	

Water inlet Ø 4" nominal

Gravity water outlet Ø 4" nominal

Pumped water outlet Ø 1-1/2" or 2" nominal



TYPICAL INSTALLATIONS

Gravity discharge to leaching field





ECOFLO[®] Polyethylene



	2.8	3.4	4.1	
	EC7-500-P-G/P	EC7-600-P-G/P	EC7-750-P-G/PDV	
Hydraulic capacity	500 US gal/d	600 US gal/d	750 US gal/d	
Length A	10' 2-3/4"	11' 7-3/4"	13' 3-1/2"	
Width B		4' 2-1/2"		
Height Includes 12" of risers	5' 9-3/4"			
Inlet height from bottom	4' 1/2"			
Gravity water outlet height 🛛 😝	1-3/4"			
Pumped water outlet height 🛛 😝	3' 8-7/8"			
Additional riser allowed	6"			
Weight Includes internal components and coco filter	1,235 lb	1,345 lb	1,455 lb	
Built-in effective volume available for dosing Pumped discharge models only	160 US gal	180 US gal	200 US gal	
Emergency storage above alarm float	545 US gal	665 US gal	760 US gal	



TYPICAL INSTALLATIONS

Gravity discharge to leaching field

Water inlet Ø 4" nominal

Ø 4" nominal





ECOFLO[®] Polyethylene



	5.7	7.3	
	EC7-1050-P-G/PDV	EC7-1350-P-G/PDV	
Hydraulic capacity	1,050 US gal/d	1,350 US gal/d	
Length 🔒	11' 3/4"	13' 5-1/2"	
Width B	6' 6-3/4"	6' 8-3/4"	
Height C	6' 3/4"		
Inlet height from bottom	4' 1-1/2"		
Gravity water outlet height 🛛 😝	4"		
Pumped water outlet height 🛛 😝	4' 3/4"		
Additional riser allowed	No additional risers allowed		
Weight Includes internal components and coco filter	2,640 lb	3,120 lb	
Built-in effective volume available for dosing Pumped discharge models only	230 US gal	295 US gal	
Total emergency storage capacity	1,155 US gal	1,595 US gal	



TYPICAL INSTALLATIONS

Gravity discharge to leaching field





ECOFLO[®] Concrete



	2.8	3.4	4.1	6.5
	EC7-500-C-G/PDV	EC7-600-C-G/P	EC7-750-C-G/PDV	EC7-1200-C-G/PDV
Hydraulic capacity	500 US gal/d	600 US gal/d	750 US gal/d	1,200 US gal/d
Length 🔒	10' 1/8"'	11' 9-3/4"	12' 7-1/4"	12' 7-1/2"
Width B	4' 2-5/8"	4' 2-5/8"	4' 4-3/4"	6' 10"
Height C	6' 5-1/4"	5' 10-7/8"	6' 8-7/8"	6' 9-1/4"
Inlet height from bottom D	4' 6"	3' 11-5/8"	4' 10"	4' 8"
Gravity water outlet height	5"	4-3/4"	5"	6"
Pumped water outlet height	4' 3-1/2"	3' 10"	5'	4' 9-3/4"
Additional riser allowed	8"			
Weight Includes tank, upper slab, internal components, and coco filter	9,900 lb	10,000 lb	15,840 lb	19,520 lb
Built-in effective volume available for dosing Pumped discharge models only	150 US gal	34 US gal	200 US gal	220 US gal
Emergency storage above alarm float	500 US gal	145 US gal	750 US gal	1,360 US gal

Check product availability with your regional representative.

Water inlet Ø 4" nominal Gravity water outlet Ø 4" nominal Pumped water outlet Ø 1-1/2" or 2" nominal



TYPICAL INSTALLATIONS

Gravity discharge to leaching field





Recommended distances

We recommend the following distance guidelines. Failure to abide by these guidelines may void the warranty of the installation.

	Polyethylene		Conorato
Reference points	2.8/3.4/4.1	5.7/7.3	Concrete
Base of excess backfill, slopes, or embankments vs. biofilter lidA	1.	3'	10'
Parking area vs. biofilter lid	1:	3'	10'
Object or structure weighing more than 500 lb (225 kg) vs. biofilter lid	13'		10'
Retaining wall vs. biofilter lid	13'		10'
Finished landscaping vs. base of biofilter lid	2"		
Seasonal high groundwater table vs. base of gravity-discharge unit	Do not install in groundwater		
Seasonal high groundwater table vs. base of pumped-discharge unit	2'	Do not install in groundwater	Up to bottom of inlet pipe



Lid clearance

Keep 2" distance between the landscape level and the top of the lid.



Components and accessories

PUMPING STATIONS

- up to 67 US gal effective dosing volume
- high-strength polyethylene

Refer to page 30 for technical information.

PUMPS

- up to 0.5 hp
- reliable and durable



Refer to page 30 for technical information.

FLOW DIVIDERS

- pressurized or gravity flow
- two to
 10 outlets





REWATEC

Integrated UV disinfection (DiUV)

Our integrated DiUV option reliably kills wastewater pathogens, allowing for safe direct discharge into a watercourse or ditch.

Wi-Fi system

Instant alerts allow us to help your client protect their investment and the environment. A service team will follow-up on any problem.

Improved design Strong, reliable parts ensure easy operation and maintenance.

New UV lamp Maximizes flow while lowering energy consumption.

Integrated pump

Discharges treated wastewater in sites of any condition and keeps ditch water out of the treatment unit.

READY TO INSTALL

We make installation fast and simple by pre-assembling and pre-wiring our UV disinfection units.

SOLUTIONS FOR ANY SITE

UV disinfection can be integrated in many polyethylene and concrete Ecoflo biofilter models. It is also available in a separate tank. Also available in stand-alone UV disinfection system



UV specifications

		REW	ATEC
Sizo	ECOFLO	rated UV ection	sinfection barate tank
5120		isinf	V di sep
POLY	(ETHYLENE	20	⊇.⊆
28	EC7-500-P-G/P	\checkmark	~
2.0	EC7-500-P-G/P-Pack	\checkmark	\checkmark
24	EC7-600-P-G/P	~	~
3.4	EC7-600-P-G/P-Pack	~	\checkmark
44	EC7-750-P-G/P	\checkmark	\checkmark
4.1	EC7-750-P-G/P-Pack	~	~
5.7	EC7-1050-P-G/P	×	\checkmark
7.3	EC7-1350-P-G/P	×	\checkmark
CON	CRETE		
2.8	EC7-500-C-G/PDV	~	\checkmark
3.4	EC7-600-C-G/P	\checkmark	\checkmark
4.1	EC7-750-C-G/PDV	~	\checkmark
6.5	EC7-1200-C-G/PDV	×	\checkmark

standard

Parameter

TREATMENT RESULTS

TSS	< 15 mg/L	4 mg/L
CBOD₅	< 15 mg/L	4 mg/L
Fecal coliforms	< 20 CFU /100 mL [†]	< 2 CFU /100 mL [†]

BNQ* effluent

DiUV

effluent

Bureau de normalization du Québec certification, similar to NSF certification.

⁺ Before photoreactivation.

RECOMMENDED **INFLUENT QUALITY**

Parameter	Level	
Iron	< 0.3 ppm (0.3 mg/L)	
Manganese	< 0.05 ppm (0.05 mg/L)	
Water hardness	< 7 gpg (120 mg/L)	

For ECC/ECP models with DiUV availability please contact your regional representative.

UV pumps

The maximum length of the pressurized pipe (flexible pipe) starting from the pump with a pipe measuring 1" (25 mm) or 1.5" (38 mm) in diameter depends on the pressure head (for instance, the difference in gradient between the base of the pump and the end of the pressurized pipe). The following table indicates the different pressurized pipe lengths allowed.

Height of the head pressure	15' (4.5 m)	10' (3 m)	5' (1.5 m)
Maximum Ø 1" (25 mm) pipe length	100' (30 m)	100' (30 m)	100' (30 m)
Maximum Ø 1.5" (38 mm) pipe length*	100' (30 m)	100' (30 m)	100' (30 m)



Champion 0.4 hp pump is for UV usage only 6.6 A, 1 phase, 60 Hz, 115 V

* Does not apply to EC-2.8-C-P model

REWATEC Nitrogen reduction (ECDn)

Safely discharge near ecologically sensitive areas with our nitrogen reduction offer that converts ammoniacal nitrogen into harmless nitrogen gas.

Septic tank (with baffle) Captures solids and clarifies wastewater. **Ecoflo biofilter**

Filters wastewater through a coconut husk fragment filter. Converts ammoniacal and organic nitrogen into nitrates.

REWATEC

Flow divider

Returns one portion of treated wastewater to the primary tank, where nitrates transform into harmless nitrogen gas. Discharges the remaining portion for final dispersal.

COMPACT SIZE

Our nitrogen reduction option is ideal for sites with limited installation space.

SOLUTIONS FOR ANY SITE

Nitrogen reduction is available with many polyethylene and concrete Ecoflo biofilter models.

TREATMENT RESULTS

Parameter	NSF 245 effluent standard	ECDn effluent
TSS	< 30 mg/L	2 ± 2 mg/L
CBOD₅	< 25 mg/L	4 ± 3 mg/L
Total nitrogen reduction	> 50%	54%
рН	6 to 9	7.1

REWATEC Nitrogen reduction (ECDn)

TYPICAL INSTALLATION



Polyethylene

Hydraulic capacity	Model	
500 US gal/d	ECDN-500-P	
	ECDN-600-P	
000 03 gai/u	ECDN-600-P-PACK	
865 US gal/d	ECDN-865-P	
1,100 US gal/d	ECDN-1100-P	

Concrete

Hydraulic capacity	Model
600 US gal/d	ECDN-600-C
1,000 US gal/d	ECDN-1000-C

REWATEC Gravity dosing distribution box

The only system that combines dosing and distribution into a single lightweight unit.



AVANTAGES

• Longevity

- Uniform dosing increases your soil absorption area's lifespan
- Flow levelers can be added to each outlet

• Two functions in one reservoir

- Adjustable dose from 12 to 18 gallons
- Gravity distribution with zero energy required
- Easy to install and maintain
 - Lighter than concrete distribution boxes
 - Access without the need for tools or dismantling

USAGE

- All septic installations that rely on gravity distribution
- Trench or bed absorption areas

EXCLUSIVE DESIGN

Water inlet	
Water miet	
Reservoir 18 gal (68 L)	
Maintenance access	
Dosing device	
Distribution chamber	I
Up to 7 lateral outlets	

TECHNICAL SPECIFICATIONS



* Protected intellectual property reference: 8296 patentmarking.premiertech.com

REWATEC[®] Pumping stations

	PSA-240	PSA-240H	
Pump	0.4 hp	0.5 hp	
Float	On/off pump switch and alarm switch		
Length of base	3' 1-	-1/2"	
Width of base 🛛 🔒	2' 10"		
Height C	4' 2"	5' 4"	
Inlet height D	2' 1"	3' 5-3/4"	
Outlet height	3' 4"		
Riser height allowed	2' 4"		
Weight	110 lb	123 lb	
Effective dosing volume	40 US gal	67 US gal	
Total volume At water inlet level	63 US gal	106 US gal	

Pumps



PERFORMANCE CURVE



Legend

- Champion 0.4 hp pump (supplied with all pumping stations) 6.6 A, 1 phase, 60 Hz, 115 V
- Champion 0.5 hp pump (supplied with all pumped Ecoflo biofilter) 8.5 A,
 1 phase, 60 Hz, 115 V





ELECTRICAL SPECIFICATION FOR FLOATS

Float switches must be used with pumps that provide integral thermal overload protection.

	Single phase		
	Maximum pump running current	Maximum pump starting current	
120 VAC 50/60 Hz	13 A	60 A	
230 VAC 50/60 Hz	12 A	60 A	

Pumps that exceed the currents in these specifications require a pump controller that will allow the stock floats to be used for signal rather than providing power.

Refer to the technical datasheet for the vault dimensions.

Float adjustments

The dose given by the on/off float depends on the length of the float stem, the length of the stem sleeve, and the position of the rubber stopper.

The factory setting will give the minimum dose. To customize the setting to accommodate local regulations or on-site requirements:

- cut a section of the stem sleeve
- lower the rubber stopper along the stem



POLYETHYLENE

	Des	ired dose volu	Astrophyses	Final		
2.8 – 500	3.4 – 600	4.1 – 750	5.7 – 1050	7.3 – 1350	Adjustment	sieeve length
21 US gal	24 US gal	26 US gal	20 US gal		None (factory setting)	4-1/2"
22 US gal	30 US gal	35 US gal	30 US gal	40 US gal	Lower rubber stopper 1/4" along stem	4-1/2"
80 US gal	95 US gal	100 US gal	85 US gal	115 US gal	Lower rubber stopper 2-1/2 " along stem*	4-1/2"
105 US gal	120 US gal	130 US gal	110 US gal	155 US gal	Make sleeve 3-1/2" long and lower rubber stopper 2-1/2 " along stem*	3-1/2"
130 US gal	150 US gal	165 US gal	140 US gal	195 US gal	Make sleeve 2-1/2" long and lower rubber stopper 2-1/2" along stem*	2-1/2"
160 US gal	180 US gal	200 US gal	175 US gal	235 US gal	Make sleeve 1-1/2" long and lower rubber stopper 2-1/2" along stem*	1-1/2"
			230 US gal	295 US gal	Remove sleeve and lower rubber stopper 2-1/2 " along stem*	0"

* Or until identification mark.

CONCRETE

Desired do	ose volume	Adjustment	Final sleeve	
2.8 - 500 4.1 - 750			length	
20 US gal	20 US gal	None (factory setting)	4-1/2"	
70 US gal	95 US gal	Lower rubber stopper 2-1/4" along stem	4-1/2"	
90 US gal	120 US gal	Make sleeve 3-1/2" long and lower rubber stopper 2-1/4" along stem*	3-1/2"	
110 US gal	140 US gal	Make sleeve 2-1/2" long and lower rubber stopper 2-1/4" along stem*	2-1/2"	
125 US gal	170 US gal	Make sleeve 1-1/2" long and lower rubber stopper 2-1/4" along stem*	1-1/2"	
150 US gal	200 US gal	Remove sleeve and lower rubber stopper 2-1/4 " along stem*	0"	

Desired dose volume 6.5 – 1200	Adjustment	Final sleeve length
95 US gal	None (factory setting)	3-1/2"
130 US gal	Make sleeve 2-1/2" long and lower rubber stopper 2-1/2" along stem*	2-1/2"
165 US gal	Make sleeve 1-1/2" long and lower rubber stopper 2-1/2" along stem*	1-1/2"
200 US gal	Make sleeve 1/2" long and lower rubber stopper 2-1/2" along stem*	1/2"
220 US gal	Remove sleeve and lower rubber stopper 2-1/2 " along stem*	0"

* Or until identification mark.

Useful links

PRO SPACE



ONLINE PURCHASE ORDER



SALES

+1 800 632-6356 info.ptwe.na@premiertech.com

ORDERS

+1 800 632-6356, ext. 16733 orders.ptwe.na@premiertech.com

MAINTENANCE AND SERVICES

+1 800 632-6356 service.ptwe.us@premiertech.com

Making a difference for our planet — for 100 years

At Premier Tech, People and Technologies have connected in lasting, transformative ways for the last 100 years, giving life to products and services that have helped to feed, protect, and improve our world.

We aren't slowing down. Premier Tech is 100 years young, and our experts continue to innovate and redefine what is possible through effective, efficient, and sustainable solutions. We are driven by our shared passion, and are committed to spend our next 100 years protecting our resources for the future.





PT Water and Environment

+1 800 632-6356 info.ptwe.na@premiertech.com PT-WaterEnvironment.com

f premiertech.canada.usa

premiertech_waterenvironment

in Premier Tech Water and Environment

Premier Tech Water and Environment

The information contained in this document was up-to-date and consistent with the information available at the time of publication. Premier Tech Ltd and its affiliated companies make no warranties or representations as to its accuracy. Because of its continuous improvement policy, Premier Tech Ltd and its affiliated companies reserve the right to change and/or discontinue the manufacture of any product and/or modify technical data and prices, for any reason whatsoever and at its sole discretion, without further notice and without liability to anyone in this regard. ECOFLO[®], REWATEC[™], PREMIER TECH[®] and PREMIER TECH & DESIGN[™] are trademarks of Premier Tech Ltd or its affiliates. For current data regarding all patent application(s) and patent(s) for the Ecoflo linear biofilter – references 1596, 2777, and 8296, or the gravity dosing distribution box – references 8296, or any part thereof, consult the website patentmarking.premiertech.com.

© 2024 Premier Tech Ltd. All rights reserved. Printed in Canada

USA 20240419